

NON-SPARKING CHAIN HOIST



EGA Master Non-Sparking Tools are the best alternative for non-sparking application purposes in potentially explosive environments. All tools are forged after casting to achieve the best quality in the market, both in mechanical properties and attractive finishing.

Allow to lift and move loads with little effort in potentially explosive environments.



Ideal for explosive atmospheres use: tankers, oil platforms, petrochemical plants, refineries, pipeline construction, offshore energy, mines, shipyards, etc

Load capacity up to 5 tons and chain length of 3 meters!



CHAIN HOIST

| COD | | Kg. | CAP | Kg. |
|-------|---------|------|-----|-----|
| Cu-Be | Al-Bron | | | |
| 71638 | 71642 | 500 | 3 m | 14 |
| 71639 | 71643 | 1000 | | 18 |
| 71640 | 71644 | 2000 | | 22 |
| 71641 | 71645 | 3000 | | 30 |
| 72141 | 72142 | 5000 | | |

TROLLEY FOR CHAIN HOIST

| COD | | CAP (Kg) | I | Kg. |
|-------|---------|----------|---------|-----|
| Cu-Be | Al-Bron | | | |
| 76693 | 76694 | 500 | 68-94 | 13 |
| 76695 | 76696 | 1000 | 68-100 | 16 |
| 76697 | 76698 | 2000 | 94-124 | 22 |
| 76699 | 76700 | 3000 | 116-140 | 24 |

Cu-Be beryllium copper

Al-Bron aluminium bronze